



Edisonstraat 34
6604 BV Wijchen The Netherlands
Tel : (0031)-(0)24-7111010
www.lebotec.nl
e-mail: info@lebotec.nl

PILING and DRILLING equipment



Groutinjection- Machine LBT-2.5-B

**Lebotec the right
Piling Machines
for a solid Foundation**



Technical data LBT-2.5-B

Type machine: Mini Drilling Rig with telescopic undercarriage for fabricating grout injection piles.

Transport width : 850 mm
Transport height (leader horizontal) : 1900 mm

Undercarriage

Width telescopic in : 850 mm
Width telescopic out : 1450 mm
Track width : 300 mm
Length undercarriage : 1540 mm

Leader

Min. length (with top) : 2030 mm
Max. length leader with all parts : 6175 mm
Max. length (with top) : 6424 mm
Max. length pile under drilling drive : 5100 mm
Racktrack : yes

Number stabilizers : 5 (3 front, 2 behind)
Powered by : Hydraulic Power pack

Drilling Drive

Total weight drilling drive : 650 kg
Weight tube clamp : 250 kg
Tube clamp \varnothing : 60 to 219 mm
Max. torque : 30 kNm
Max. drive speed (*) : 80
Total weight rig incl. drilling drive : 5550 kg
Operating : Manual or Remote-controlled
Min/max ambient temperature in service : -10/+35 C

Weights can vary with the final configuration of the machine.

Other versions on request

* (Depending on used hydraulic powerpack)

