



Edisonstraat 34
6604 BV Wijchen
Tel : (0031)-(0)24-7111010
www.lebotec.nl
e-mail: info@lebotec.nl

PILING and DRILLING equipment

Drilling Rig LBT 20-12-B



**Lebotec the right
Piling and Drilling Rigs
For a solid Foundation**

Technical data LBT-20-12 B

Type machine: Drilling Rig for fabricating concrete screw piles.

Max. vertical drilling length	:	10.5	meter
Max. weight drilling drive	:	0.66	ton
Max. torque	:	50	kNm (full length)
Weight drilling drive	:	1.25	ton
Leader length total	:	13.1	meter (incl. foot, extensions and top)
Length leader foot	:	0.11	meter
Length 1 ^e leader part (basic section):	:	9.8	meter
Length 2 ^e leader part	:	1.0	meter
Length 3 ^e leader part	:	1.0	meter
Length/height leader top	:	1.1	meter
Main dimension leader	:	500x450	mm
Leader stroke	:	3500	mm (vertical 1,1 m above tot 2.4 m below ground level)
Max degree hoisting forward	:	10	°
Max hoisting capacity	:	4,0	ton
Capacity main winch (pull up)	:	4,0	ton (16 ton pull up)
Capacity winch (pull down)	:	4,0	ton
Capacity auxiliary winch	:	2,0	ton
Motor	:	4	cylinder diesel
Power / Rpm	:	73.4	kW (98 HP) by 2000 rpm
Max. torque	:	374	Nm by 1600 rpm
Electric system	:	24	V DC
Transport width	:	2690	mm
Undercarriage center to center	:	3050	mm
Length undercarriage totally	:	3750	mm
Width tracks	:	700	mm
Number of track rollers	:	7	/ each site
Ballast extendable 1000mm	:	1.1	ton
Total weight excl. drilling drive	:	19.3	ton
Total weight incl. drilling drive	:	20.8	ton

Other versions on request

There may be to the listed specifications not legally binding because during the development of machines certain specifications can be changed without written notice.
Subject to printing errors.

